

Warewashing Pot&Pan Washer with Automatic Hood and Front/Side Feeding, Multi-Rack Support 1433mm

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



506066 (EPPWEALMS)

Pot&Pan Washer, automatic hood, front/side feeding with multi-rack support

Short Form Specification

Item No.

304 AISI stainless steel front and side panels, wash tank, tank filter and wash and rinse arms. Double skinned, insulated, hood with automatic opening and closing with safety switch. N. 4 washing cycles and a self-cleaning cycle. Built-in atmospheric, insulated water boiler (10,5 kW), 18-liter capacity, combined with rinse booster pump guarantee a constant hot rinse temperature of 84°C. Boiler with 304 welding for protection against corrosion. Wash Safe Control assures the correct water temperature and pressure during the rinse phase to guarantee a perfect rinsing performance independent from the water pressure in the network (min. 0,5 bar). Thermometer. Electronic control board with digital display. Pre-arrangements for connection to an automatic detergent dispenser. Direct through-feed using loading/unloading tables or front-feed loading. Cell dimensions mm730x660x625h (WXDXH). Load capacity: n.6x1/1 GN. Supplied with: n. 1 basket in stainless steel and n. 2 racks for containers and trays.

Main Features

- Simple service from the front.
- 4 washing programs (one program is continual).
- Atmospheric insulated boiler combined with the rinse booster pump for perfect rinsing results (water temperature and pressure always constant during rinsing cycles), independent from the inlet water pressure.
- Automatic start on hood closure.
- Direct through-feed using loading or unloading tables or front-feed loading.
- Large strainer boxes above the water surface and extra strainer in the tank bottom at the pump inlet.
- Self-cleaning cycle to automatically sanitize the dishwasher after use.
- Automatic hood opening and closing through safety switch.
- Final rinse only starts when the correct temperature has been reached (waiting device).
- Pre-arrangements for automatic detergent and rinse-aid dispenser.
- Electronic control panel and digital display.
- Adjustable pressure for the lower wash system, according to the weight of the items being washed.
- Automatic boiler empty button.
- Low noise level.
- Easy to remove wash/rinse arms for cleaning.

Construction

- Unit to feature smooth surfaces to facilitate cleaning.
- Finished in top quality materials to ensure durability.
- 304 AISI stainless steel front and side panels, wash tank, tank filter and wash and rinse arms.
- No pipes inside the washing chamber.
- Double-walled construction reduces the levels of noise and heat emitted.
- Double rack support suitable to use also standard rack of 500x500mm.

Included Accessories

- 2 of Extra rack for containers and trays PNC 864182
- 1 of Extra stainless steel basket for pot washer 1300mm PNC 864190

Optional Accessories

- Integrated HACCP kit ☐ PNC 864001
- Filter for partial demineralization ☐ PNC 864017
- Kit to measure total and partial water hardness ☐ PNC 864050
- Extra rack for containers and trays ☐ PNC 864182
- Extra stainless steel basket for pot washer 1300mm ☐ PNC 864190

APPROVAL: _____


- Filter for total demineralization ☐ PNC 864367
- Kit for trays in Potwashers ☐ PNC 864471




Electrolux
PROFESSIONAL

**Warewashing
Pot&Pan Washer with Automatic Hood and
Front/Side Feeding, Multi-Rack Support
1433mm**

Front




Side



- CWI = Cold Water inlet 1 (cleaning)
D = Drain
EI = Electrical inlet (power)
EO = Electrical Outlet
HWI = Hot water inlet
WI = Water inlet

Top



Electric

Supply voltage:

506066 (EPPWEALMS) 400 V/3N ph/50 Hz

Default Installed Power: 15.5 kW

Electrical power max.: 26 kW

Total Installed Power: 26 kW

Boiler heating elements:

Wash pump power: 5 kW

Rinse pump power: 0.28 kW

Water:

Pressure, bar min/max: 0.5-7 bar

Water supply temperature*: 50 °C

Boiler Capacity (lt): 18

Washing tank capacity (lt): 110

Washing cycle electrical elements: 10.5 kW

Hot rinse cycle duration (sec.): 20

Min hot rinse water consumption (lt/cycle):** 7.7

Rinsing water consumption (per cycle): 7.7 lt

Key Information:

Washing cycle temperature: 55-65 °C

Hot rinse cycle temperature: 84 °C

Working cycles time (sec.): 180/360/540/inf

N° of working cycles: 4 (180/360/540/inf)

Cell dimensions - width: 730 mm

Cell dimensions - depth: 660 mm

Cell dimensions - height: 625 mm

External dimensions, Width: 1433 mm

External dimensions, Height: 1760 mm

External dimensions, Depth: 890 mm

Net weight: 270 kg

Noise level: <70 dBA



**Warewashing
Pot&Pan Washer with Automatic Hood and Front/Side Feeding, Multi-
Rack Support 1433mm**
The company reserves the right to make modifications to the products
without prior notice. All information correct at time of printing.

2020.09.15